




<b>SILVERFLEX</b>					
<p>PVC coated polyester fabric with helical steel wire reinforcement. More flexible than Tuflex.</p>	NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	WALL	Coil Length (m)
	51	2	102	0.5+/-0.1	10
	76	3	152	0.5+/-0.1	10
	102	4	204	0.5+/-0.1	10
<p>Colour / Silver Temperature Range / 0°C to 70°C Material / PVC Coated Polyester</p>	127	5	254	0.5+/-0.1	10
	152	6	304	0.5+/-0.1	10
	178	7	356	0.5+/-0.1	10
	203	8	406	0.5+/-0.1	10
	229	9	458	0.5+/-0.1	10
	254	10	508	0.5+/-0.1	10
	305	12	610	0.5+/-0.1	5
	356	14	712	0.5+/-0.1	5
	381	15	762	0.5+/-0.1	5
	406	16	812	0.5+/-0.1	5
	457	18	914	0.5+/-0.1	5
	508	20	1016	0.5+/-0.1	5
	559	22	1118	0.5+/-0.1	5
	600	24	1220	0.5+/-0.1	5



<b>INDUSTROFLEX</b>					
<p>Industroflex is a highly flexible, retractable ducting eminently suitable for the rapid movement of high volume air blowing.</p>	NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	PITCH	Coil Length (m)
	127	5	254	1 <sup>1/2</sup>	5
	152	6	305	1 <sup>1/2</sup>	5
	178	7	356	1 <sup>1/2</sup>	5
<p>Colour / Blue with Red Spiral Temperature Range / -30°C to 120°C Material / Blue Neoprene coated fabric with a red wear strip</p>	203	8	406	2	5
	229	9	458	2	5
	254	10	508	2	5
	280	11	560	3	5
	305	12	610	3	5
	356	14	712	3	5
	381	15	762	3	5
	406	16	812	3	5
	457	18	914	3	5

