



BLOWER DUCT




Blower duct is lightweight, extremely flexible ducting. Constructed from PE coated fabric and has hanging eyelets. Ideal for positive pressure portable ventilation units to service man holes, tanks, marquees etc.

Colour / Blue / White / Yellow
Temperature Range / 0 °C to 85 °C
Material / PE coated fabric

NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	PITCH	Coil Length (m)
152	6	152	1 ^{1/2}	5, 10
178	7	178	1 ^{1/2}	5, 10
203	8	203	2	5, 10
229	9	229	2	5, 10
254	10	254	2	5, 10
280	11	280	3	5, 10
305	12	305	3	5, 10
356	14	356	3	5, 10
381	15	381	3	5, 10
406	16	406	4	5, 10
457	18	457	4	5, 10
508	20	508	4	5, 10



INSULATED BLOWER DUCT



Insulated blower duct is also available in White for heated or refrigerated air. For light suction duties this product is also available with a narrower pitch.

Colour / White ONLY
Temperature Range / 0 °C to 85 °C
Material / PE coated fabric

NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	PITCH	Coil Length (m)
152	6	152	1 ^{1/2}	5, 10
178	7	178	1 ^{1/2}	5, 10
203	8	203	2	5, 10
229	9	229	2	5, 10
254	10	254	2	5, 10
280	11	280	3	5, 10
305	12	305	3	5, 10
356	14	356	3	5, 10
381	15	381	3	5, 10
406	16	406	4	5, 10
457	18	457	4	5, 10
508	20	508	4	5, 10

