



# Chemflow Range AS2594

The Chemflow range is suitable for the suction and delivery of a wide range of Chemicals. Constructed of polypropylene films and fabrics the hoses are resistant to most acids, alkalis and solvents. Internal and external helix wires bind

the hose together and deliver its pressure handling characteristics and a tough PVC coated fabric cover forms the outer cover. Temperature Rating: -20°C to +100°C.

## Chemiflow Standard Code 951 - grey with red stripe

NOM Inches	I.D (mm)	O.D (mm)	Min. Bend Radius (mm)	Working Pressure Mpa @ 20°C	Weight (kg/m)	Coil Lengths (m)
1"	25	38	100	1.4	0.9	20
1¼"	32	45	125	1.4	1.3	20
1½"	39	50	140	1.4	1.5	20
2"	51	65	170	1.2	1.8	20
2½"	63	78	200	1.0	2.7	20
3"	76	92	270	1.0	3.3	20
4"	102	120	340	1.0	6.3	20


Internal Wire - Polypropylene Coated Galvanised Steel. External Wire - Galvanised Steel



## Chemiflow SSW Code 952- grey with red stripe

NOM Inches	I.D (mm)	O.D (mm)	Min. Bend Radius (mm)	Working Pressure Mpa @ 20°C	Weight (kg/m)	Coil Lengths (m)
1"	25	38	100	1.4	0.9	20
1¼"	32	45	125	1.4	1.3	20
1½"	39	50	140	1.4	1.5	20
2"	51	65	170	1.2	1.8	20
2½"	63	78	200	1.0	2.7	20
3"	76	92	270	1.0	3.3	20
4"	102	120	340	1.0	6.3	20


Internal Wire - Polypropylene Coated Galvanised Steel. External Wire - Stainless Steel



## Chemiflow CS Code 969- orange with blue stripe

NOM Inches	I.D (mm)	O.D (mm)	Min. Bend Radius (mm)	Working Pressure Mpa @ 20°C	Weight (kg/m)	Coil Lengths (m)
1"	25	38	100	1.4	0.9	20
1¼"	32	45	125	1.4	1.3	20
1½"	39	50	140	1.4	1.5	20
2"	51	65	170	1.2	1.9	20
2½"	63	78	200	1.0	3	20
3"	76	92	270	1.0	3.4	20
4"	102	120	340	1.0	6.5	20
6"	152	180	700	1.0	12.4	to order

Internal Wire - Stainless Steel. External Wire - Galvanised Steel



## Chemiflow ASS- grey with red stripe / orange with blue stripe

NOM Inches	I.D (mm)	O.D (mm)	Min. Bend Radius (mm)	Working Pressure Mpa @ 20°C	Weight (kg/m)	Coil Lengths (m)
1"	25	38	100	1.4	0.9	20
1½"	39	50	140	1.4	1.5	20
2"	51	65	170	1.2	1.8	20
2½"	63	78	200	1.0	2.7	20
3"	76	92	270	1.0	3.3	20
4"	100	120	340	1.0	6.3	20
6"	152	180	700	1.0	12.2	To Order

Internal Wire - Stainless Steel. External Wire - Stainless Steel

