

FLEXFLOW						
Flexflow is constructed from neoprene rubber coated polyester fabric and reinforced with a spring wire helix. Recommended for heavy duty and higher temp applications.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
		39	1 ^{1/2}	80	1.5	10
		51	2	102	1.5	10
		57	2 ^{1/4}	114	1.5	10
		63	2 ^{1/2}	126	1.5	10
		76	3	152	1.5	10
		83	3 ^{1/4}	166	1.5	10
		89	3 ^{1/2}	178	1.5	10
		102	4	204	1.5	10
		114	4 ^{1/2}	228	1.5	10
		127	5	254	1.5	10
		152	6	304	1.5	10
		178	7	356	1.5	5
		203	8	406	1.5	5
		229	9	458	1.5	5
		254	10	508	1.5	5
		280	11	560	1.5	5
		305	12	610	1.5	5
		356	14	712	1.5	5
		381	15	762	1.5	5
		406	16	812	1.5	5
		457	18	914	1.5	5

ABRASFLEX						
Abraflex is constructed from neoprene rubber coated polyester fabric and has a natural rubber lining. It is recommended for heavy duty and higher temp applications.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
		51	2	306	0.3	10
		63	2 ^{1/2}	378	0.3	10
		76	3	456	0.3	10
		89	3 ^{1/2}	534	0.3	10
		102	4	612	0.3	10
		114	4 ^{1/2}	684	0.3	10
		127	5	762	0.3	10
		152	6	912	0.3	10
		178	7	1068	0.3	5
		203	8	1218	0.3	5
		229	9	1374	0.3	5
		254	10	1524	0.3	5
		280	11	1680	0.3	5
		305	12	1830	0.3	5
		356	14	2136	0.3	5
		406	16	2436	0.3	5
		457	18	2742	0.3	5

All sizes made to order.

