

## The Future of

## **Hose Technology**

Barfell Nominal Working Coil Pres. @ 20°C Wall **Product** Weight Lengths Nominal Code 0.D. Mpa P.S.I. Grams/m Thickness in Metres

## **NYLON**



Wall Available in Black and Natural (Translucent)

Nylon pressure tubing is made from premium quality raw materials and precision engineered to ensure simplicity of connections with fittings and adaptors.

F	lexible Me	etric					
2	05500	4mm	0.65 mm	2.0	290	7.6	100
2	05505	5mm	0.85 mm	2.0	290	11.8	100
2	05510	6mm	1.0 mm	2.0	290	16.6	100
2	05515	8mm	1.4mm	2.0	290	30.9	100
2	05520	10mm	1.7mm	2.0	290	47.2	100
2	05525	12mm	2.0 mm	2.0	290	66.8	100
F	lexible Im	perial					
	05530	1/8"	0.019"	1.7	250	4.4	100
2	05535	3/16"	0.013"	1.7	250	10.0	100
2	05540	1/4"	0.040"	1.7	250	17.7	100
2	05545	5/16"	0.049"	1.7	250	26.9	100
2	05550	3/8"	0.058"	1.7	250	39.7	100
2	05555	1/2"	0.076"	1.7	250	68.6	100
2	05560	5/8"	0.065"	0.9	125	80.4	100
2	05565	3/4"	0.080"	0.9	125	117.1	100
S	emi Rigid	Imperial -	Black Only				
	05600	3/16"	0.039"	4.3	625	12.5	100
2	05605	1/4"	0.050"	4.3	625	21.6	100
2	05610	5/16"	0.062"	4.3	625	33.8	100
2	05615	3/8"	0.074"	4.3	625	48.5	100
2	05620	1/2"	0.097"	4.3	625	87.1	100
S	elf Store						
2	05000	6	0.8	1.2	174	20.5	30
2	05005	10	1.1	1.2	174	39.5	30
2	05010	12.5	1.6	1.2	174	77.2	30

Wall Available in Yellow

Applications Pneumatic and hydraulic control systems, fuel tubing, air and gas tubing. Also ideal for handling weed killing solutions, refrigerants, fresh and sea water, fumigants, paints and lacquers and many other products.